

Camera	Model	FNK-HP2B720AE
	Sensor	1.3MP 1/3" CMOS Sensor
	Min. Illumination	Color : 0.2Lux @F1.6 B/W: 0.01 Lux @F1.6(B/W IR-ON)
	Shutter Time	1/50(1/60)s to 1/10,000s
	Lens	2.0MP HD Lens
	Lens Mount	M14
	Day & night	IR-Cut Filter with Auto Switch
	Image	Max. Resolution
Frame Rate		PAL: 960P@25fps NTSC: 960P@30fps
Setting		Saturation, Brightness & Contrast are Adjustable Through IE Browser or Client Software.
Compression	Video Compression	H.264 High Profile, JPEG Snapshot
	Bite Rate	0.1Mbps~6Mbps
	Audio Compression	G.711a
Network	Storage	Network Storage
	Alarm	Motion Detection, Video loss, Video Block, etc.
	Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, (HTTPS, SIP, 802.1x, IPv6 option)
	Features	Anti-flicker, Dual-stream, Heartbeat, Password Protection
Interface	Ethernet	1*10/100Mbps Ethernet Port, RJ45 port
	Audio I/O	1/0 (RCA)
General	Temperature	-10℃ - + 60℃
	Humidity	10%-90% RH
	Power Supply	DC12V±10%
	IR Range	30 Meters
	Consumption	MAX 5W
	Ingress Protection	IP66
	Dimension & Weight	208(W)*70mm(H) & 500g