

Model :				
 				
D1 (2MP/2K/2.5K)				
Unit Weight	0.57kg			
Unit Size	200*200*120mm			
Carton size	54.5*43*59.5cm			
Qty	30pcs			
FCL weight	19.5kg			
Product function introduction				
<p>* 1.5-inch outdoor weatherproof dual-light dome camera (8 infrared leds and 8 white light leds) with high-definition pixels, clear and delicate images</p> <p>* Support cloud storage and local TF card video storage to ensure safe storage of video data</p> <p>* Wifi connection, scan the QR code to easily connect the camera and the network, the operation is simple and convenient</p> <p>* Built-in high-sensitivity MIC and speaker, support two-way voice intercom</p> <p>* AI humanoid & motion detection, accurate alarm, APP alarm push, support remote viewing on iOS or Android</p> <p>* Horizontal rotation of 350 degrees, vertical rotation of 90 degrees</p>				
Product specification				
System	definition	2MP	2K	2.5K
	System structure	Embedded Linux real-time operating system		
	Video processing	H.264 video encoding	H.264/H.265 video encoding, support dual stream	H.264/H.265 video encoding, support dual stream
Video	Image output	1920*1080@15fps	2304*1296@20fps	2560*1440@20fps
	Lens	3.6mm		
	Shutter	Automatic shutter		
	Pan/Tilt	355° left and right 90° up and down		
	Day and night mode	IR-CUT infrared filter type		
	Noise reduction	Support 2D/3D noise reduction		
	Wide dynamic	Support digital wide dynamic		
	Image flip	Support horizontal and vertical flip		
Audio	Audio processing	G.711 codec standard, support audio and video synchronization		
	Audio port	1 input, level 2Vp-p, impedance 1kΩ, support MIC/pickup input; 1 output, impedance 8Ω, 1W output power		
Storage Management	Recording mode	Manual recording, motion detection recording, timing recording, alarm recording		
	Video storage	Micro SD card storage/cloud storage		
	Playback, backup	support		
	Alarm trigger	Motion detection; push alarm information; support mobile phone, client remote		
	Reset button	Support		
Network	Wired network	Support		
	Wireless network	802.11b/g/n		
	Supporting agreement	Support NI protocol		
Power	power supply	Power supply: DC12V/2A		
Working Environment	Installation location	Homes, shops, schools, factories;		
	Installation method	Lay flat, wall-mounted, hoisted		
	Operating temperature	-10℃ - +55℃		
	Working humidity	10%-90%		
Packing List	Camera	1pcs		
	Manual	1pcs		
	Screw pack	1pcs		